




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H04L	A2	(11) International Publication Number: WO 97/41661 (43) International Publication Date: 6 November 1997 (06.11.97)
(21) International Application Number: PCT/US97/06161 (22) International Filing Date: 16 April 1997 (16.04.97) (30) Priority Data: 08/639,457 29 April 1996 (29.04.96) US (71) Applicant: MOTOROLA INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US). (72) Inventor: DORENBOS, David; 241 N. Larch, Elmhurst, IL 60126 (US). (74) Agents: LUKASIK, Susan, L. et al.; Motorola Inc., Intellectual Property Dept., 1303 East Algonquin Road, Schaumburg, IL 60196 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: USE OF AN ENCRYPTION SERVER FOR ENCRYPTING MESSAGES**(57) Abstract**

An encryption server receives a first encrypted message (105) and decrypts (403) the encrypted message using a first key, yielding a decrypted message comprising a second encrypted message (105A), an identification of a sender of the first encrypted message, and an identification of a first recipient. The second encrypted message, the identification of the sender, and the identification of the first recipient are determined (405) from the decrypted message. The second encrypted message and the identification of the sender are encrypted (409) with a second key, yielding a third encrypted message (109). The third encrypted message (109) is transmitted to the first recipient.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5 USE OF AN ENCRYPTION SERVER FOR ENCRYPTING MESSAGES

Field of the Invention

10 This invention relates to communication systems, including but not limited to encrypted communication systems.

Background of the Invention

15 Encrypted voice and data communication systems are well known. Many of these systems provide secure communications between two or more users by sharing one or more pieces of information between the users, which permits only those users knowing that information to properly decrypt the message. This information is known as the encryption key, or
20 key for short. Encryption keys may be private keys, where a single key is utilized for encryption and decryption, or public keys, where multiple keys are utilized for encryption and decryption.

25 Methods of encrypting using public-key encryption are well known in the art. Typically, a public-key encryption is a method of encryption by which a single message is encrypted using a sender's private key and then a recipient's public key. The recipient then decrypts the message using the recipient's private key and then the sender's public key. Typically, public keys are 512 bits long, although some public keys have as few as 256 bits.
30 Some encryption experts recommend using 1024-bit keys. Because the computational power required to break a key increases exponentially with the length of the key, longer keys provide more security. In addition, because two keys are needed to decrypt a message, two longer keys are more difficult to decrypt if neither key is known.

35

Today, secure communication systems are used to transmit data in an encrypted fashion. If a user wishes to send the same message to five different recipients, the user must encrypt the message five different times, each time using the public key of a different recipient for the message. The user then transmits the five messages to the five recipients. Such a process, however, is troublesome when the user wishes to transmit to, for example, 100 or more recipients. In this instance, the user must encrypt each message individually 100 or more times, one for each recipient. If the user has a portable communication device, such as a laptop computer, the user's battery may run out of power before encryption and transmission of each message has occurred. In addition, the encryption and transmission process can consume a lot of time and processing power for the portable device, rendering the portable device unavailable for other activities by the user during the encryption and transmission time period. Thus, such transmissions would be impractical for portable users.

Accordingly, there is a need for a method of transmitting encrypted data messages to multiple users without resulting in a time or power barrier to the user's communication device.

20

Brief Description of the Drawings

FIG. 1 is a block diagram of a communication system having an encryption server in accordance with the invention.

FIG. 2 is a block diagram of an encryption server in accordance with the invention.

FIG. 3 is a flowchart showing a method of transmission of a digital data message to an encryption server in accordance with the invention.

FIG. 4 is a flowchart showing a method of transmission of an encrypted message by an encryption server in accordance with the invention.

Description of a Preferred Embodiment

The following describes an apparatus for and method of using an encryption server for encrypting messages. Messages are encrypted twice, once with the sender's private key and then with an encryption server's public key before transmission of the messages to the encryption server. The encryption server decrypts received messages with the encryption server's private key, yielding an encrypted message, a user identification (ID), and one or more recipient IDs. The encryption server encrypts the encrypted message and the user ID individually with each of the recipient's public keys and transmits the resultant message(s) to the appropriate recipient. Each recipient decrypts the messages using the recipient's private key and the sender's public key. A secure communication system is thereby provided, wherein portable communication devices are neither tied up nor drained of power because the device's user wishes to send a single encrypted message to multiple recipients.

A method of using an encryption server for encrypting messages comprises the steps of, at a communication unit operated by a user generating a digital data message. The digital data message is encrypted using a first key, yielding a first encrypted message. An identification of the user and an identification of a first recipient are appended to the first encrypted message, yielding an appended first encrypted message. The appended first encrypted message is encrypted using a second key, yielding a second encrypted message. The second encrypted message is transmitted to an encryption server. At the encryption server, the second encrypted message is received. The second encrypted message is decrypted using a third key, yielding the appended first encrypted message. The first encrypted message, the identification of the user, and the identification of the first recipient are determined from the appended first encrypted message. The first encrypted message and the identification of the user are encrypted with a fourth key, yielding a third encrypted message. The third encrypted message is transmitted to the first recipient. In the preferred embodiment, the first key is a private key associated with the user, the second key is a public key associated with the encryption server, the third key is a private key associated with the encryption server, and the fourth key

is a public key associated with the first recipient. Alternatively, the second key and the third key may be identical. The transmitting steps may be performed over wireless communication resources, such as radio frequency communication resources, or wireline communication resources, such as
5 standard telephone lines or fiber optic cable.

In addition, the step of appending may further comprise the step of appending an identification of a second recipient to the first encrypted message, thereby yielding the appended first encrypted message. In this
10 case, the method further comprises the steps of encrypting, by the encryption server, the first encrypted message and the identification of the user with a fifth key, yielding a fourth encrypted message, and transmitting the fourth encrypted message to the second recipient. In the preferred embodiment, the fifth key is a public key associated with the second
15 recipient. Alternatively, the step of appending may comprise the step of appending three or more identifications of recipients to the first encrypted message, thereby yielding the appended first encrypted message.

A block diagram of a communication system having an encryption
20 server is shown in FIG. 1. An encryption server 101 is shown at the center of FIG. 1. Further details of the encryption server 101 are shown in FIG. 2 described below. A user of a first communication unit 103 utilizes the first communication unit 103 to generate an digital data message that is encrypted in two stages in the preferred embodiment. In the first stage, the
25 digital data message is encrypted using a first key, which is the user's private key in the preferred embodiment. The result of this encryption is a first-stage encrypted message. (In an alternate embodiment, the digital data message is not encrypted using the first key.) The user's identification (ID) and one or more recipient IDs are appended to the first-stage encrypted
30 message, yielding an appended message. The appended message is encrypted using a second key, yielding a second-stage encrypted message 105. In the preferred embodiment, the second key is the public key associated with the encryption server 101. The communication unit transmits the second-stage encrypted message 105 to the encryption server
35 via a wireless communication link to a wireless communication device 107, such as a radio frequency (RF) base station, repeater, or radio, or infrared

communication device. The second-stage encrypted message 105 is conveyed by the wireless communication device 107 to the encryption server 101.

5 The encryption server 101 decrypts the second-stage encrypted message 105 using an appropriate key. In the preferred embodiment, the appropriate key is the encryption server's private key. The encryption server 101 then determines the user's ID from the decrypted message and also determines the IDs of all recipients that the user indicated as intended
10 targets of the first-stage encrypted message. The encryption server 101 then encrypts the user's ID along with the first-stage encrypted message by encrypting with the public key of the first recipient. The resultant message 109 is transmitted to the first recipient, who utilizes communication unit 111. The encryption server then encrypts the first-stage encrypted message
15 along with the user's ID by encrypting with the public key of the second recipient and transmitting the resultant encrypted message 113 to the second recipient, who utilizes communication unit 115. This process continues until the encryption server reaches the last recipient ID on the user's list, and encrypts the first-stage encrypted message along with the
20 user's ID by encrypting with the public key of the last recipient and transmitting the resultant encrypted message 117 to the last recipient, who utilizes communication unit 119.

 The encryption server 101 may also receive user requests for encryption
25 from wireline communication devices 121 via wireline channels. As with the wireless transmission, the encryption server decrypts the received message 123 using the private key of the encryption server, then encrypts the resultant message individually for each different recipient using the appropriate recipient's individual public key. These recipients may be
30 wireline devices 127 and 131, which receive the messages 125 and 129 via wireline communication channels.

 The above examples describe RF to RF transmission and wireline to wireline transmission of encrypted messages. Nevertheless, the method of
35 the present invention is equally successful if a wireline device 121 requests transmission to wireless communication units 111, 115, and 119. Similarly,

a wireless communication unit 103 may request transmission from the encryption server 101 to wireline communication devices 127 and 131. In addition, the recipients may be a combination of both wireless and wireline communication units 111, 115, 119, 127, and 131, regardless of whether the sender uses a wireless communication unit 103 or a wireline communication device 121.

Upon receipt of the encrypted message from the encryption server, each recipient decrypts the message with the recipient's own private key, and after determining the user's ID, decrypts the resultant message with the user's public key, thereby yielding the original digital data message. The user is also referred to as the sender of the (second-stage) encrypted message 105.

A block diagram of an encryption server 101, including its input signals 105 and output signals 109, 113, 125, and 117, is shown in FIG. 2. In the preferred embodiment, the encryption server 101 is a Sun SparcServer2000 in a multiprocessor configuration, available from Sun Microsystems. The encryption server 101 comprises one or more processors 201, such as microprocessors or digital signal processors, as are well known in the art. The processors 201 have access to encryption and decryption algorithm(s) 203, a public key data base 205, and memory 211. The encryption/decryption algorithms 203 include public key algorithms, private algorithms, and other algorithms as may be used in the art. The public key data base 205 includes a list of IDs, as used by senders (users) and recipients, and the public keys associated with each of these IDs. The memory 211 includes programming and other data as is necessary to provide functionality as described herein for the encryption server 101. A receive block for wireline and wireless communications 207 and a transmit block for wireline and wireless communications 209 are also connected to the processors 201. The receive block for wireline and wireless communications 207 performs appropriate demodulation techniques on received messages 105 and 123. The transmit block for wireline and wireless communications 209 performs appropriate modulation techniques on messages 109, 113, 124, and 117 to be transmitted. In addition, the encryption server 101 may be equipped with hardware

and/or software to provide the encryption server 101 with over-the-air-rekeying capabilities.

As shown in FIG. 2, a user message 105 comprises a second-stage
5 encrypted (encrypted using the encryption server's public key) message comprising the digital data message 105A, first-stage encrypted with the user's (sender's) private key, in addition to the user ID and a number of recipient IDs. Alternatively, the user message 105 may comprise an
unencrypted digital data message 105A, the user ID, and one or more
10 recipient IDs. The user message 105 is input to the receive wireline/wireless block 207, the output of which is input to the processor(s) 201. The processor(s) 201 utilize(s) the encryption/decryption algorithm(s) 203 and the public key data base 205 to decrypt the message 105 using the
private key of the encryption server. The processor(s) 201 then determine(s)
15 the first-stage encrypted message 105A, the user ID, and the first recipient ID from the decrypted message. The processor(s) 201 then determine(s) the first recipient's public key from public key data base 205, and the encrypt the first-stage encrypted message 105A and the user ID by using the
encryption/decryption algorithms 203 and the first recipient's public key.
20 The processor(s) 201 then append(s) the first recipient ID, thereby yielding a message 109 that is sent to the transmit wireline/wireless block 209 for transmitting to the first recipient's communication unit 111, as shown in FIG. 1. A similar process is performed on the first-stage encrypted
message (or unencrypted digital data message) 105A and the user ID for
25 each of the recipients listed in the user's message 105.

In an alternate embodiment, the encryption server 101 may be physically distributed as one or more encryption servers. In this embodiment, the encryption server 101 encrypts the message using a second set of private
30 and public keys associated with a second server. The message so encrypted is transmitted to the second encryption server. The second server decrypts the message and then encrypts the message using the public key(s) of the recipient(s). When traffic is heavy, the encryption server 101 may optimize its efficiency by determining the computation required to transmit directly
35 to each recipient or transmit the request to one or more distributed servers. This process is transparent to the user.

The flowchart of FIG. 3 shows a method for use by a communication unit in transmitting a digital data message to an encryption server 101. At step 301, a digital data message is generated. If at step 303 the digital data message is not to be encrypted, the process continues with step 307. If at
5 step 303 the digital data message is to be encrypted, the process continues with step 305, where the digital data message is encrypted using the private-key of the user who wishes to communicate the message. At step 307, it is determined if the IDs of the user and/or recipient(s) are to be encrypted. If
10 the IDs are to be encrypted, the process continues with step 309, where the user ID and recipient ID(s) are appended to the encrypted message from step 305 or the unencrypted message from step 301 if no encryption took place. At step 311, the message from step 309, including the appended IDs, is encrypted using the public key of the encryption server 101. The process
15 continues with step 317, where the encrypted message is transmitted to the encryption server 101. If at step 307 the IDs are not to be encrypted, the process continues with step 313, where the encrypted message of step 305 (or the unencrypted message from step 301 if no encryption took place) is encrypted with the public key of the encryption server 101. At step 315, the
20 user ID and recipient ID(s) are appended to the encrypted message of step 313, and the process continues with step 317.

In an alternative embodiment, i.e., when the digital data message is not to be encrypted at step 303 of FIG. 3, the sender or user may decrypt the
25 digital data message and, if desired, the recipient IDs only once, using the encryption server's public key. The encryption server then decrypts the message using the encryption server's private key, and encrypts the message individually for each of the recipients with the recipient's public key. The recipient then decrypts the message using only the recipient's
30 private key. This method requires the user to locally store only one public key, the key of the encryption server. With this method, a single symmetrical key may be used to encrypt and decrypt the messages between the user and the encryption server 101, and one or more keys may be used to encrypt the messages between the encryption server and the recipient.
35 Nevertheless, for better security, the encryption server 101 engaged in this embodiment should be a physically secured, e.g., locked away with limited

access, because unencrypted information is present inside the encryption server 101. An advantage of such a system includes enabling law enforcement officials the ability to read the decrypted message as available in the encryption server 101.

5

The flowchart of FIG. 4 shows the method performed by the encryption server 101 in accordance with the present invention. At step 401, the encryption server receives the encrypted message transmitted by the communication unit 103. At step 403, the encryption server decrypts the
10 message received at step 401 with the private key of the encryption server 101. At step 405, the encryption server determines the user ID, the recipient ID(s), and the encrypted (generated at step 305 of FIG. 3) or unencrypted (generated at step 301 of FIG. 3) data message. In an alternate embodiment, the encryption server 101 may be equipped with the
15 appropriate keys to decrypt the digital data message 105A (when the message 105A is encrypted) so that law enforcement agencies may have full access to all information transmitted in the system.

At step 407, it is determined if the IDs (i.e., the user ID and/or recipient
20 ID(s)) are to be encrypted before transmission. If the IDs are to be encrypted, the process continues with step 409, where the encryption server encrypts the encrypted data message along with the user ID, and the recipient's ID if desired, with the recipient's public key. At step 411, the encryption server transmits the encrypted message to the recipient whose
25 public key was used at step 409. If at step 413 there are more recipients identified by the user to which the encryption server has not yet encrypted and transmitted the message, the process continues with step 407. If there are no more recipients at step 413, the process ends. If at step 407, the IDs are not to be encrypted, the process continues with step 415, where the
30 encrypted data message is encrypted with the recipient's public key, and the user ID and the recipient's ID are appended to that encrypted message without further encryption, and the process continues with step 411.

Optionally, all messages may be encrypted at one time, and then
35 transmitted in succession at one time, rather than encrypting a first message with one public key, then transmitting the encrypted first message

right away, then encrypting a second message using another public key, and transmitting the encrypted second message immediately, and so forth.

5 The above text and associated drawings describe a method using public-key encryption. Private-key encryption, where the same key is used to encrypt and decrypt a message, may also be used. For example, the key used to encrypt the message send to the encryption server may be the same or identical key used to decrypt the encrypted message at the encryption server. In addition, the encryption method employed by the user to encrypt
10 the original digital data message 105A may also be private-key encryption, rather than public-key encryption. In addition, a different encryption algorithm may be utilized for the user's first stage of encryption than for the user's second stage of encryption, the result of which is transmitted to the encryption server.

15

In the above manner, the encryption server encrypts the user's data message individually for each different recipient using that particular recipient's public key. The encryption server has more computing resources available to it than an individual communication unit, and can
20 encrypt and transmit a message multiple times to many different users in a more efficient manner than can an individual communication unit. Individual communication units need not store all possible recipient's public keys, but instead need store only the encryption server's public key. Encryption of the recipient's ID(s) helps to secure the identity of the
25 recipient(s) and eliminates a source of information for traffic analysis by undesired readers/interceptors of such information.

What is claimed is:

Claims

1. A method comprising the steps of:
 - 5 at a communication unit operated by a user:

generating a digital data message;

encrypting the digital data message using a first key, yielding a first
10 encrypted message;

appending an identification of the user and an identification of a first
recipient to the first encrypted message, yielding an appended first
encrypted message;
15 encrypting the appended first encrypted message using a second key,
yielding a second encrypted message;

transmitting the second encrypted message to the encryption server,
20 wherein the encryption server is not the first recipient.
- 25 2. The method of claim 1, wherein the first key is a private key associated
with the user and wherein the second key is a public key associated with the
encryption server.
- 30 3. The method of claim 1, wherein the step of appending further comprises
the step of appending an identification of a second recipient to the first
encrypted message, thereby yielding the appended first encrypted message.

4. A method comprising the steps of:

at an encryption server:

5 receiving a first encrypted message;

decrypting the encrypted message using a first key, yielding a decrypted message comprising a second encrypted message, an identification of a sender of the first encrypted message, and an identification of a first

10 recipient;

determining the second encrypted message, the identification of the sender, and the identification of the first recipient from the decrypted message;

15 encrypting the second encrypted message and the identification of the sender with a second key, yielding a third encrypted message;

transmitting the third encrypted message to the first recipient.

20

5. The method of claim 4, wherein the first key is a private key associated with the encryption server and wherein the second key is a public key
25 associated with the first recipient.

6. The method of claim 4, further comprising, when a second identification of a second recipient is part of the decrypted message, the steps of
encrypting, by the encryption server, the second encrypted message and the
30 identification of the sender with a third key, yielding a fourth encrypted message, and transmitting the fourth encrypted message to the second recipient.

7. A method comprising the steps of:

at a communication unit operated by a user:

5 generating a digital data message;

encrypting the digital data message using a first key, yielding a first encrypted message;

10 encrypting the first encrypted message using a second key, yielding a second encrypted message;

appending an identification of the user and an identification of a first recipient to the second encrypted message, yielding an appended second
15 encrypted message;

transmitting the appended second encrypted message to the encryption server;

20 at the encryption server:

receiving the appended second encrypted message;

determining the second encrypted message, the identification of the user, and the identification of the first recipient from the appended second
25 encrypted message;

decrypting the second encrypted message using a third key, yielding the first encrypted message;

30

encrypting the first encrypted message with a fourth key, yielding a third encrypted message;

transmitting the third encrypted message to the first recipient.

35

8. The method of claim 7, wherein the step of appending further comprises the step of appending an identification of a second recipient to the second encrypted message, thereby yielding the appended second encrypted message.

5

9. The method of claim 7, wherein the first key is a private key associated with the user, wherein the second key is a public key associated with the encryption server, wherein the third key is a private key associated with the encryption server, and wherein the fourth key is a public key associated with the first recipient.

10

10. The method of claim 7, wherein the identification of the user is encrypted using the second key before the step of appending.




FIG. 1





FIG. 2


3/4

FIG. 3



4/4

FIG. 4






INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 9/00		A3	(11) International Publication Number: WO 97/41661
			(43) International Publication Date: 6 November 1997 (06.11.97)
(21) International Application Number: PCT/US97/06161 (22) International Filing Date: 16 April 1997 (16.04.97) (30) Priority Data: 08/639,457 29 April 1996 (29.04.96) US (71) Applicant: MOTOROLA INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US). (72) Inventor: DORENBOS, David; 241 N. Larch, Elmhurst, IL 60126 (US). (74) Agents: LUKASIK, Susan, L. et al.; Motorola Inc., Intellectual Property Dept., 1303 East Algonquin Road, Schaumburg, IL 60196 (US).			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 11 December 1997 (11.12.97)

(54) Title: USE OF AN ENCRYPTION SERVER FOR ENCRYPTING MESSAGES

(57) Abstract

An encryption server receives a first encrypted message (105) and decrypts (403) the encrypted message using a first key, yielding a decrypted message comprising a second encrypted message (105A), an identification of a sender of the first encrypted message, and an identification of a first recipient. The second encrypted message, the identification of the sender, and the identification of the first recipient are determined (405) from the decrypted message. The second encrypted message and the identification of the sender are encrypted (409) with a second key, yielding a third encrypted message (109). The third encrypted message (109) is transmitted to the first recipient.




FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/06161

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :H04L 9/00 US CL :380/49, 25 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 380/49, 25 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) APS search terms: server, append, identification, id		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,479,514 A (KLONOWSKI) 26 December 1995 (26/12/95), see abstract and column 2, lines 1-22.	1-10
A, P	US 5,574,785 A (UENO ET AL) 12 November 1996 (12/11/96), see figure 1.	1-10
A	US 5,455,865 A (PERLMAN) 03 October 1995 (03/10/95), see figure 1 and figure 4a.	1-10
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* "A"	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E"	earlier document published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	"G" document member of the same patent family
"P"	document published prior to the international filing date but later than the priority date claimed	
Date of the actual completion of the international search 29 SEPTEMBER 1997		Date of mailing of the international search report 24 OCT 1997
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer  CARMEN D. WHITE Telephone No. (703) 306-4177

Form PCT/ISA/210 (second sheet)(July 1992)*




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 9/00		A3	(11) International Publication Number: WO 97/41661
			(43) International Publication Date: 6 November 1997 (06.11.97)
(21) International Application Number: PCT/US97/06161		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 16 April 1997 (16.04.97)			
(30) Priority Data: 08/639,457 29 April 1996 (29.04.96) US			
(71) Applicant: MOTOROLA INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US).			
(72) Inventor: DORENBOS, David; 241 N. Larch, Elmhurst, IL 60126 (US).			
(74) Agents: LUKASIK, Susan, L. et al.; Motorola Inc., Intellectual Property Dept., 1303 East Algonquin Road, Schaumburg, IL 60196 (US).		<p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	
		(88) Date of publication of the international search report: 11 December 1997 (11.12.97)	

(54) Title: USE OF AN ENCRYPTION SERVER FOR ENCRYPTING MESSAGES

(57) Abstract

An encryption server receives a first encrypted message (105) and decrypts (403) the encrypted message using a first key, yielding a decrypted message comprising a second encrypted message (105A), an identification of a sender of the first encrypted message, and an identification of a first recipient. The second encrypted message, the identification of the sender, and the identification of the first recipient are determined (405) from the decrypted message. The second encrypted message and the identification of the sender are encrypted (409) with a second key, yielding a third encrypted message (109). The third encrypted message (109) is transmitted to the first recipient.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		